



MARKET LEADER[†]



#1 LIGHT TRUCK
REPLACEMENT
TIRES[†]

#1 ORIGINAL
EQUIPMENT
CONSUMER TIRES[†]

WRANGLER[®] WORKHORSE[®] AT THE TOUGHNESS TO TAME THE TERRAIN

■ RUGGED FOR THE ROAD AHEAD

Go where work takes you, thanks to a tread compound built to handle tough conditions while resisting chipping and chunking.

■ WEATHER THE STORM

Handle the demands of the job, even in deep snow, with a tire that has the three-peak mountain snowflake designation.

■ OVERCOME THE CONDITIONS

When facing tough jobs, count on a tough tread with large blocks and open grooves that dig in and help you make it through the day.



WRANGLER[®] WORKHORSE[®] AT CARGO VAN SIZES



SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTIONS WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD SINGLE (LBS)	MAX LOAD DUAL (LBS)	TREAD DEPTH (IN 32NDS)	REVS/ MILE
235/65R16C	121/119R	E	BSL	481195855	243461	6.5 - 7.5	7.0	9.8	28.0	3,195	3,000	11	743
LT225/75R16	115/112R	E	BSL	481748855	240859	6.0 - 7.0	6.0	8.8	29.3	2,680	2,470	15	710
LT245/75R16	120/116S	E	BSL	481103855	240863	6.5 - 8.0	7.0	9.8	30.5	3,042	2,778	15	682
LT245/70R17	119/116S	E	BSL	481120855	240862	6.5 - 8.0	7.0	9.8	30.6	3,000	2,755	15	680

POPULAR FITMENTS

• Ram ProMaster

• Ford Transit

• Mercedes Sprinter



PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death. Servicing locations can be found by visiting: www.GoodyearFleetNetwork.com [†] Source: Modern Tire Dealer (2023 Jan Facts Issue) - 2022 Replacement Passenger & Light Truck Tire Brand Market Shares (p. 36); 2022 North American OE Consumer Tire Market Share Totals (p. 38).

For more complete information, go to Tire-HQ[™] at www.tire-hq.com. ©2023 The Goodyear Tire & Rubber Company. All rights reserved.



MARKET LEADER[†]



#1 LIGHT TRUCK[†]

#1 ORIGINAL
EQUIPMENT TIRES[†]

WRANGLER[®] WORKHORSE[®] HT

THE STRENGTH TO GO THE EXTRA MILE

- BUILT FOR THE LONG HAUL**
Ride with a tire that gives you longevity for tough days, hard work and jobs done right.
- WEAR THEM WELL**
Every hardworking driver should get where they're going with a smooth, confident ride.
- WORK NO MATTER THE WEATHER**
Be there rain, sleet or shine with tires that help move water out of the way for enhanced braking in wet conditions.
- AS TOUGH AS YOU ARE**
Engineered to give you toughness, stability and wet traction to help you get the job done.



WRANGLER[®] WORKHORSE[®] HT CARGO VAN SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTIONS WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD SINGLE (LBS)	MAX LOAD DUAL (LBS)	TREAD DEPTH (IN 32NDS)	REVS/ MILE
195/75R16C	107/105R	D	VSBL	131196995	244634	5.0 - 6.0	5.5	7.7	27.5	2,150	2,040	11	756
225/75R16C	121/120R	E	VSBL	131194995	244633	6.0 - 7.0	6.0	8.8	29.3	3,195	3,085	11	710
235/65R16C	121/119R	E	VSBL	131195995	244632	6.5 - 7.5	7.0	9.8	28.0	3,195	3,000	11	743
LT225/75R16	115/112R	E	BSL	131748875	241635	6.0 - 7.0	6.0	8.8	29.3	2,680	2,470	14	714
LT245/75R16	120/116R	E	BSL	131747875	241640	6.5 - 8.0	7.0	9.8	30.5	3,042	2,778	14	686
LT245/70R17	119/116R	E	BSL	131469875	241634	6.5 - 8.0	7.0	9.8	30.6	3,000	2,755	14	684

POPULAR FITMENTS

- Ram ProMaster
- Ford Transit
- Mercedes Sprinter



PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death. Servicing locations can be found by visiting: www.GoodyearFleetNetwork.com. † Source: Modern Tire Dealer (2023 Jan Facts Issue) - 2022 Replacement Passenger & Light Truck Tire Brand Market Shares (p. 36); 2022 North American OE Consumer Tire Market Share Totals (p. 38). *Valve stem and balance are not included.

For more complete information, go to Tire-HQ™ at www.tire-hq.com. ©2023 The Goodyear Tire & Rubber Company. All rights reserved.